



REGENESIS[®]


REMTECH
Europe

The use of Passive Flux Meters and Design Verification Program - Lessons Learned from Pre-Application Assessments at In Situ Remediation Sites

Gareth Leonard
RemTech 2019



Introduction



Design Verification Testing (DVT): What is it?

- **Design Verification Tests (DVTs):**
 - A process of data collection and analysis
 - to verify design assumptions of a site's
 - chemical and geological conditions and
 - the viability of *in-situ* injection(s).
- **Focus on remedial design parameters**
 - Not necessarily Site Investigation parameters
- **High density sampling**
- **Data collection of concern varies site to site**
- **Performed 4-6 weeks prior to an application:**
 - Allow time for analysis and modification



Design Verification Testing (DVT): Why do it?

Focus


- Site investigations typically focus on liability and risk assessment
 - Emphasis on contaminant identification, plume dimensions and pathways
 - This isn't a criticism!
- Design verification focuses on efficient reagent-contaminant contact
 - Emphasis on identification of principal impacted units, contaminant mass distribution and reagent delivery



Design Verification Testing (DVT): Why do it?



Advantages

- Identify technical blind spots/gap analysis
- Refines design assumptions
- Calibrate Reagent Design
 - Contaminant mass vs reagent volume/mass
 - Consider competing compounds
 - Can we fit reagent volumes in the target zone
 - Reagent selection
 - Improves contact with contaminant:
 - Improves efficacy
 - Improves accuracy of dose and application
 - Make most cost effective application
 - Proof of concept





Design Verification Testing (DVT): Components

- Confirmation of geology in treatment zone
 - Continuous soil core logging
 - Settling tubes
- Identification of flux zones
 - Sampling as above
 - Passive flux meter
 - Hydraulic Profile Testing
- Contaminant concentrations in flux zones
 - 'Real' contaminant concentrations to be addressed
 - MIP
 - Multi-level sampling
 - Passive flux meter





Design Verification Testing (DVT): Components

- Geochemical confirmation
 - Competing contaminants
 - Competing organics e.g. DOC = competitive sorption
- Clear water Injection
 - Test aquifer and application parameters
- Pilot injection
 - Test emplacement as well as efficacy





Focus on passive flux meters

- Petroleum hydrocarbon plume, up to 1000ug/L
- Sands and gravels
- 1km (partially active) pump and treat barrier
- Concept was to replace with a colloidal activated carbon barrier
- DVT to define treatment thickness and contaminant mass at barrier location
- Including Passive Flux Meter (I-Flux)
 - 2 wells
 - Multi-level sampling
 - At each:
 - 1 cartridge for groundwater flow
 - 1 cartridge for contaminant flux



Focus on passive flux meters



- Very high groundwater flow rate (10-30 m/DAY at approx. 20mBGL)
- Corresponding to Pump and Treat
- Low contaminant concentrations
- Vertical extent more than expected

Result:

- Barrier needs to be deeper
- Need to test with pumps off
- Review design to allow for higher flow
- Pilot in the right area?

Depth of boundary pump

Low flow velocity corresponding to a fine soil layer in log


Design Verification: Clear Water Injection Test

- Injection of clean water to test:
 - Total volume accepted by the aquifer
 - Flowrates accepted
 - Pressure required
 - Minimum and 'maximum' (without fracturing)
 - Documents acceptance rates and volumes vertically
- Assists in application decisions
 - High or low volume substrate?
 - Direct Push Injection
 - Top-down vs Bottom-up
 - Injection wells
 - Screened Intervals
 - Balance of low pressure vs radius of influence



Bottom-up injection tool with un-retracted sheath

Bottom-up injection tool with retracted sheath




Pilot injection example



- Generally flat, slight slope downward toward the south
- Superficial geology: sand and gravel
- Non-continuous clay layer at ~ 8m bgs
- 2nd deeper clay layer in some areas at ~15-20 m bgs
- GW at ~ 6 mbgs and flows south toward Au Sable River, ~1km away

Total PFAS Results: 132 Days Post-application




Design verification testing: analysis


- Multiple site study:
 - 43 Sites
- Project Design Approach
 - 33 % source areas
 - 67 % mid- to distal- plume
- Contaminant Type
 - 35% Petroleum
 - 61% CVOC's
 - 4% Comingled
- General Soil Type
 - 50% Fine grained (Clays & Silts)
 - 50% Coarse grained (Sand & Gravel)



Design Verification Testing - Results



ANALYSIS OF TECHNICAL BLIND SPOTS



Conclusions

- Enhances knowledge of treatment location/zone
- Improves accuracy and granularity of data on which the design is based
- Allows gap analysis of knowledge
- Tests assumptions of the design
- Produces data directly relevant to the application
- Improves confidence
- Avoids errors
- Reduces overall costs
- Increases overall success of the project

Thank you

Gareth Leonard
Managing Director, Europe
REGENESIS
+44 (0) 1833 630 411

gleonard@regenesisc.com

REMTECH
Europe

